



**ELECTRIC HIGH PRESSURE UNIT (21 LPM  
AT 160 BAR)**

**€2.750,00**

Removes light fouling from hulls, propellers  
and underwater surfaces  
Big cartridge filter at pump inlet  
Motor thermal protection

---

**SKU:** HDE160\_21

**Categories:** [High Pressure Units](#)

**Tags:** [CW200](#), [Economic](#), [Electric](#)

**PRODUCT DESCRIPTION**

Electric motor 5.5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 160 bar (5.5 gpm at 2320 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)

**SPECIFICATIONS**

|                                |   |
|--------------------------------|---|
| <b>Brand</b>                   | DiveWise Equipment  |
| <b>Power (kW)</b>              | 5.5   |
| <b>Power (HP)</b>              | 7.5   |
| <b>Design pressure (bar)</b>   | 160   |
| <b>Design pressure (psi)</b>   | 2320  |
| <b>Flow (LPM)</b>              | 21  |
| <b>Flow (GPM)</b>              | 5.5   |
| <b>RPM</b>                     | 1500  |
| <b>Drive</b>                   | Electric  |
| <b>Dimensions (LxWxH) (mm)</b> | 850x540x950   |
| <b>Lenght (mm)</b>             | 850   |
| <b>Lenght (inch)</b>           | 33.5  |
| <b>Width (mm)</b>              | 540   |
| <b>Width (inch)</b>            | 21.3  |
| <b>Height (mm)</b>             | 950   |
| <b>Height (inch)</b>           | 37.4  |
| <b>Weight (kg)</b>             | 185   |
| <b>Weight (lbs)</b>            | 407.9   |
| <b>Application</b>             | Underwater cleaning of light fouling                      |
| <b>Voltage</b>                 | 400VAC 3-phase  |
| <b>Optional</b>                | Connection and control for extern selfpriming pump 220vac |
| <b>CE Certified</b>            | Yes   |
| <b>SIR Certified</b>           | Optional  |