



DIESEL HIGH PRESSURE UNIT (21 LPM AT 160 BAR) (COPY)

Removes light fouling from hulls, propellers and underwater surfaces
Big cartridge filter at pump inlet
Motor thermal protection

SKU: HDMD160-21

Categories: [High Pressure Units](#)

Tags: [CW200](#), [Economic](#), [Petrol](#)

PRODUCT DESCRIPTION

Diesel motor 10 HP / 4 wheels with air tyres / Max. 1560 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 160 bar (5.5 gpm at 2230 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Weight 105kg / Dimensions L x W x H: 950x680x950mm

SPECIFICATIONS

Brand	DiveWise Equipment
Power (kW)	9,6
Power (HP)	13,1
Design pressure (bar)	160
Design pressure (psi)	2900
Flow (LPM)	21
Flow (GPM)	5.5
RPM	1560
Drive	Diesel
Dimensions (LxWxH) (mm)	950x680x950
Lenght (mm)	950
Lenght (inch)	37.4
Width (mm)	680
Width (inch)	26,8
Height (mm)	950
Height (inch)	37.4
Weight (kg)	105
Weight (lbs)	231,49
Application	Underwater cleaning of medium fouling
CE Certified	Yes
SIR Certified	Optional