



**ELECTRIC HIGH PRESSURE PRO CART  
WITH WATERCOOLED FREQUENCY  
INVERTER 30KW | 300 BAR/43 LPM**

**€23.629,00**

Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8 | Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22

---

**SKU:** HDE30-300-43-PRO

**Categories:** [High Pressure Units](#)

**Tags:** [Electric](#), [PRO Cart](#)

## PRODUCT DESCRIPTION

Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8 | Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22

**SPECIFICATIONS**

|                                  |                    |
|----------------------------------|--------------------|
| <b>Type pump</b>                 | PRO-T22            |
| <b>Dimensions (LxWxH) (inch)</b> | 47,2×29,5×35,4     |
| <b>Brand</b>                     | DiveWise Equipment |
| <b>Power (kW)</b>                | 30                 |
| <b>Power (HP)</b>                | 40,8               |
| <b>Design pressure (bar)</b>     | 300                |
| <b>Design pressure (psi)</b>     | 4350               |
| <b>Flow pump (LPM)</b>           | 43                 |
| <b>Flow pump (GPM)</b>           | 11,4               |
| <b>Flow (LPM)</b>                | 43                 |
| <b>Flow (GPM)</b>                | 11,4               |
| <b>RPM</b>                       | 1450               |
| <b>Engine/motor power</b>        | 30                 |
| <b>Drive</b>                     | Electric           |
| <b>Engine / Motor</b>            | Nicolini           |
| <b>Direction of rotation</b>     | CW                 |
| <b>RPM shaft</b>                 | 1450               |
| <b>Gear ratio</b>                | 1                  |
| <b>Pump speed</b>                | 1450               |
| <b>Dimensions (LxWxH) (mm)</b>   | 1200x750x900       |
| <b>Lenght (mm)</b>               | 1200               |
| <b>Lenght (inch)</b>             | 47.3               |
| <b>Width (mm)</b>                | 750                |
| <b>Width (inch)</b>              | 29,6               |
| <b>Height (mm)</b>               | 900                |
| <b>Height (inch)</b>             | 35.5               |

|                     |  |
|---------------------|--|
| <b>Weight (kg)</b>  | 325  |
| <b>Weight (lbs)</b> | 716,6  |
| <b>Application</b>  | Drilling, Grinding, Underwater cleaning of heavy fouling |
| <b>Voltage</b>      | 3-phase 400VAC / 50 Hz (optional 440VAC / 60 Hz)         |