



**ELECTRIC HIGH PRESSURE UNIT (21 LPM
AT 250 BAR)**

€4.450,00

Removes light fouling from hulls, propellers
and underwater surfaces
Big cartridge filter at pump inlet
Motor thermal protection

SKU: HDE250_21

Categories: [High Pressure Units](#)

Tags: [CW300](#), [Economic](#), [Electric](#)

PRODUCT DESCRIPTION

Electric motor 8,8 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 250 bar (5,5 gpm at 3625 psi) / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Weight 161kg) / Dimensions: 900x750x950mm

SPECIFICATIONS

| | |
|--------------------------------|---|
| Brand | DiveWise Equipment |
| Power (kW) | 8,8 |
| Power (HP) | 12 |
| Design pressure (bar) | 250 |
| Design pressure (psi) | 3625 |
| Flow (LPM) | 21 |
| Flow (GPM) | 5.5 |
| RPM | 1500 |
| Drive | Electric |
| Dimensions (LxWxH) (mm) | 900x750x950 |
| Lenght (mm) | 900 |
| Lenght (inch) | 35.5 |
| Width (mm) | 750 |
| Width (inch) | 29,6 |
| Height (mm) | 950 |
| Height (inch) | 37.4 |
| Weight (kg) | 161 |
| Weight (lbs) | 355 |
| Application | Drilling, Grinding, Underwater cleaning of medium fouling |
| Voltage | 400VAC 3-phase |
| CE Certified | Yes |
| SIR Certified | Optional |