



PETROL HIGH PRESSURE UNIT (30 LPM AT 280 BAR)

€9.150,00

Big cartridge filter at pump inlet Adjustable pressure valve Electric start, thermal protection and hour counter

SKU: HDMP280_30

Categories: <u>High Pressure Units</u>

Tags: CW250, CW300, CW350, DR200,

GR200, Petrol, Semi PRO, SR450

PRODUCT DESCRIPTION

Engine Mo33,5Petrol driven, 2 cilinder Aircooled Honda GX690 / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. 30 LPM at 280 bar (7,9 gpm at 4060 psi) / / Gearbox driven pump / Electrical starting / No engine-oil safety device (oil-alert) / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification / Weight 150kg / Dimensions 1000x820x850mm



SPECIFICATIONS

Brand DiveWise Equipment

Design pressure (bar) 280

Design pressure (psi) 4060

Flow (LPM) 30

Flow (GPM) 7.9

RPM 1500

Drive Petrol

Engine / Motor 2 cilinder Aircooled Honda GX690

Lenght (mm) 1000

Lenght (inch) 39,4

Width (mm) 820

Width (inch) 32,3

Height (mm) 850

Height (inch) 33.5

Weight (kg) 150

Weight (lbs) 330,8

Application Drilling, Grinding, Underwater cleaning of heavy fouling

CE Certified Yes

SIR Certified Optional