



**SEMI PRO KIT WITH CW350 CAVITATION GUN AND DIESEL HIGH PRESSURE UNIT (30 LPM AT 280 BAR)**

Complete set for cavitation cleaning.  
Including:  
High Pressure gun  
Semi PRO Pump  
50 meter Neutrally Buoyant hose  
Supply pump

---

**SKU:** HDMD280\_30, CW350T1, DE149-08-HS24M-HM24M-50000, EWSP230

**Categories:** [Cleaning kit](#)

**Tags:** [Cleaning kit](#), [Diesel](#), [Semi PRO](#)

## PRODUCT DESCRIPTION

Semi PRO cavitation cleaning kit for removing medium to hard fouling, including:

CW350T1 Zero-Thrust Long Cavitation Cleaning gun (Max. 40 LPM at 300 bar)

Ergonomic handgun / Handle with safety latch / Swiveling hose inlet connection / Stainless steel lance protection / Tapered lance end with red marking / Max. recommended working pressure 300 bar (4350 psi) / Maximum flow 40 LPM (10,5 gpm) / Safety ring shield on lance around nozzle / CE certified / SIR certified / According to IMCA guidelines / Lance length 668mm / Retro lance length 700mm / Weight 2300 gram (under water 1200 gram) / Optional adjustable lance handle

HDMD280\_30 Diesel High Pressure Unit (30 LPM at 280 bar)

Diesel driven, 2 cilinder Aircooled KohlerKDW1003 / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 30 LPM at 280 bar (7,9 gpm at 4060 psi) / CE certified / Gearbox driven pump / Electrical starting / Automatic decelerator to reduce the number of revs in the bypass phase / No engine-oil safety device (oil-alert) / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Weight 285kg) / Dimensions 1370x850x1020mm

DE149-08-HS24M-HM24M-50000 1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) - 50 mtr  
1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) / 50 mtr / Quick-connect couplings /  
Recommended for ROV cavitation cleaning

EWSP230 Electric water supply pump 230V

Electric water supply pump 230VAC with 10 meter 1" hose / quick-connect couplings / 270W /  
270mm x 200mm x 435mm / 15.8 kg

**SPECIFICATIONS**